HIGHWAY PAVEMENT MARKING (USDOT-FHWA) STANDARD ALPHABET AND SYMBOLS FOR

**PAVEMENT MARKINGS** 

SHEET 4 OF 7

1205.08

**ENGLISH** 

STANDARD

DRAWING

FOR

STATE OF IZ-06
NORTH CAROLINA
DEPT. OF TRANSPORTATION
DIVISION OF HIGHWAYS
RALEIGH, N.C.

## **GENERAL NOTES:**

- 1- STANDARD CHARACTERS ARE 25 GRID UNITS HIGH AND 4 UNITS WIDE (EXCEPT LETTER "I" AND THE NUMBER "1" WHICH ARE 1 UNIT WIDE).
- 2- VERTICAL STROKES ARE 1 UNIT WIDE, HORIZONTAL STROKES ARE 4 UNITS HIGH.
- 3- SPACE 1 UNIT (MIN.) BETWEEN CHARACTERS OR AS OTHERWISE SHOWN (OPTICAL SPACING MAY BE USED).
- 4- STANDARD CHARACTER HEIGHTS ARE  $8^\prime\text{-}4^{\prime\prime}.$  EXCEPT FOR THE  $6^\prime$  RAILROAD 'R' SYMBOL AND THE TWO-LANE  $10^\prime\text{-}5^{\prime\prime}$  SCHOOL SYMBOL.
- 5- FOR 8'-4" HIGH CHARACTERS, THE WIDTH IS 16" (USE 4" FOR EACH GRID SQUARE).
- 6- FOR 10'-5" HIGH CHARACTERS, THE WIDTH IS 20" (USE 5" FOR EACH GRID SQUARE).
- 7- FOR 6' HIGH CHARACTERS, THE WIDTH IS  $11\frac{1}{2}$ " (USE  $2\frac{7}{8}$ " FOR EACH GRID SQUARE).

FOR FOR SYMBOLS MARKINGS DRAWING AND STANDARD **ALPHABET PAVEMENT** ENGLISH

NORTH CAROLINA DEPT. OF TRANSPORTATION DIVISION OF HIGHWAYS RALEIGH, N.C. STATE NORTH CAF - 06

> HIGHWAY PAVEMENT MARKING (USDOT-FHWA) STANDARD

SHEET 4 OF 7 1205.08